

SIZE	RIM WIDTH	OD +/-2%	SECTION WIDTH	CARRY CAP. 6MPH	WEIGHT	UNIVERSAL #	NON-MARKING #
15x4.5-8	3	14.5	4.5	1260	20	26903101	26903102
400x6 Rib	3.25	10.5	4	-	8	26140401	26140402
400x8 Rib	3.75	16.1	4.5	-	26	26165401	26165402
16x6-8	4.33	15.9	5.3	1310	34	26910101	26910102
500x8	3	18	4.8	-	37	26218101	26218102
500x8	3.25	18	4.8	-	37	26220101	26220102
500x8Rib	3.75	18	5.2	-	40	26240401	26240402
18x7-8	4.33	18.1	6.4	3750	49	26915101	26915102
600x9 SMOOTH	4	21	5.7	4230	60	26300001	26300002
600x9	4	21	5.7	4230	60	26300101	26300102
21x8-9	6	19.75	7.25	6190	72	26925101	26925102
650x10	5	23	6.8	5810	82	26330101	26330102
23x9-10	6.5	22	8	7525	98	26930101	26930102
23x10-12	8	23	8.8	8820	115	26935101	26935102
700x12 SMOOTH	5	26.1	6.9	6640	110	26400001	26400002
700x12	5	26.1	6.9	6640	110	26400101	26400102
27x10-12	8	26	9.75	4320	159	26940101	26940102
700x15-(29x8-15)	5.5	29.1	7.5	7905	139	26410101	26410102
700x15	6	29.1	7.64	-	152	26420101	-
750x15	5.5	29.5	7.34	8630	156	26510101	26510102
750x15	6.5	29.5	7.87	10195	156	26520101	26520102
750x16	5.5	31.25	7.25	8615	175	26530101	26530102
800x16	5.5	32.5	8.1	8800	195	26560101	26560102
815x15-(28x9-15)	7	28	8.6	9000	139	26580101	26580102
825x15 SMOOTH	6.5	32.5	8.8	10875	215	26610001	26610002
825x15	6.5	32.5	8.8	10875	215	26610101	26610102
28x12.5-15	9.75	27.75	11.62	10085	196	26835101	26835102
825x15	6.5	32.5	8.8	10875	215	26610101	26610102
200x50-10	6.5	17	10	9530	51	26845101	26845102
250x15	7	29	9.6	9615	178	26950101	26950102
250x15	7.5	29	10	10300	178	26952101	26952102
300x15	8	32.3	10.8	13190	257	26955101	26955102
10.00x20	7	39.25	9	16800	309	26780101	-
10.00x20	7.5	39.25	9	16900	309	26785101	26785102
10.00x20	8	39.25	9	17015	309	26790101	26790102
12.00x20	8	42.3	10	18605	417	26810101	26810102
12.00x20	8.5	42.3	10	18605	417	26815101	26815102

**SOLID SOLVER RESILIENT TIRE EF CLICK\***

SIZE	RIM WIDTH	O.D. +/-2%	TREAD DEPTH	SECTION WIDTH	CARRY CAP. 6MPH	WEIGHT	UNIVERSAL#	NON-MARKING #
15x4.5-8	3	14.5	4	4.5	1260	20	26904101	26904102
16x6-8	4.33	15.9	5.3	5.7	1310	34	26910101	26910102
18x7-8	4.33	18.1	5.6	6.4	3750	49	26916101	26916102
21x8-9	6	19.75	7	7.25	3750	72	26926101	26926102
650x10	5	23	6.1	6.7	5810	82	26331101	26331102
23x9-10	6.5	23	7.2	8	4210	98	26931101	26931102
27x10-12	8	26	8.6	9.75	4320	159	26941101	26941102
600x9	4	21	5.1	5.7	4230	62	26301101	26301102
700x12	5	26.1	6.4	6.9	6640	114	26401101	26401102
815x15	7	28	7.9	8.6	9000	139	26581101	26581102
28x12.5-15	9.75	27.75	8	9	10085	196	26836101	26836102
825x15	6.5	32.5	8.8	9.5	10875	215	26611101	26611102
200x50-10	6.5	17	7.25	10	9530	51	26846101	26846102
250x15	7	29	9	9.6	9615	178	26951101	26951102
250x15	7.5	29	9	9.6	10300	178	26953101	26953102
300x15	8	32.3	9.75	10.8	13190	257	26956101	26956102

**SOLID SOLVER Resilient Tire X-FLEX and X-FLEX EF CLICK\***

SIZE	RIM WIDTH	O.D. +/-2%	SECTION WIDTH	CARRY CAP. 6MPH	WEIGHT	UNIVERSAL#	NON-MARKING #
------	-----------	------------	---------------	-----------------	--------	------------	---------------

500x8	3	17.75	5	2670	32	26218901	26218902
600x9	4	20.5	6.25	4230	60	26300901	26300902
600X9EFClick	4	20.5	6.25	4230	60	26301901	-
650x10	5	22.5	7.12	5810	76	26330901	26330902
700x12	5	26.25	7.75	6640	110	26400901	26400902
700X12EFClick	5	26.25	7.75	6640	97	26401901	26401902
815X15	7	27	7.25	9000	136	26580901	26580902
815x15EFClick	7	27	7.25	9000	144	26581901	-
825X15	6.5	31	7.5	10875	178	26610901	-
825x15EFClick	6.5	31	7.5	10875	178	26611901	26611902
300x15	8	32	11	13190	257	26955901	-
300x15EFClick	8	32	11	13190	257	26956901	-
250X15	7	28	9.5	9615	160	26950901	-
250X15EFClick	7	28	9.5	9615	160	26951901	-

